

Omico Mining Corp.

Namibia's Next Copper Mine



Disclaimer



The information in this document ("Document") has been prepared by Omico Mining Corp Ltd ("Omico" or the "Company"), is confidential and is provided to you for introductory discussion purposes only and to enable you to evaluate your interest in the opportunity referred to in it. Each recipient of the Document ("you"), by accepting it, agrees that you will not, and none of your employees, directors, agents, officers, advisers, associates and other representatives (together "Representatives") will, copy, reproduce, distribute or otherwise disclose to others at any time the whole or any part of the Document without the prior written consent of the Company, and that you and your Representatives will keep confidential the Document and any information otherwise obtained from the Company and will use the Document and such other information solely to evaluate a possible investment in the Company. However, the Document should not be considered as an offer or invitation to subscribe for, or purchase, any securities in the Company or as any inducement to make an offer or invitation with respect to any such securities. The information in the Document does not and is not intended to constitute any 'valuation', 'formal valuation', 'appraisal', 'prior valuation', or a 'report, statement or opinion of an expert' for the purposes of any securities legislation in the UK or elsewhere, nor as constituting any financial product advice, or advice or opinion concerning tax, accounting or legal matters. The Document does not take account of any person's investment objectives, financial situation or particular needs. No agreement to subscribe for or purchase securities in the Company will be entered into on the basis of the Document.

The Document contains forecasts, projections and forward looking information, which are not a guarantee of future performance and involve known and unknown risks and uncertainties. Actual results and developments are likely to differ materially from those expressed or implied. Factors which could cause such material differences include, without limitation, fluctuations in market prices of metals and other commodities, exchange rate fluctuations, results of future exploration and development, future costs, availability of capital, changes in economic, social, political or market conditions, and changes in the regulatory environment. The Company has not audited or investigated the accuracy or completeness of the information, statements or opinions contained in the Document. Accordingly, to the maximum extent permitted by applicable laws, the Company makes no representation and gives no assurance, guarantee or warranty, express or implied, as to, and takes no responsibility and assumes no liability for, the authenticity, validity, accuracy, suitability or completeness of, or any errors in or omissions from, any information, statements or opinions contained in the Document. You should not act, or refrain from acting, in reliance on the Document. The information in the Document does not purport to be all-inclusive or contain all information you may require in order to make an informed assessment of the future prospects of the Company. You should conduct your own investigation and analysis in order to satisfy yourself as to any matters referred to in the Document or otherwise, before making any investment decision.

- Omitiomire Copper: Highlights



Significant Copper Resource

- M&I Resource 81.2 Mt @ 0.60% Cu, 490Kt Cu metal
- 304 km² exploration license (renewable for a further 6 years)
- Supporting 25-30ktpa Cu cathode production
- 13-15 years LOM
- Production and LOM upside

ESG

- Low water consumption (90m3/t cathode) in closed circuit
- Minimal negative social impact no relocations, etc.
- 800-1,000 direct jobs created
- Estimated Scope 1&2 CO₂ emissions 3,700kg CO₂/t
 cathode

Low Development Risk

- BFS well advanced design 80% and engineering 75% complete
- Conventional open pit, proven chloride heap leach and SXEW
- Readily available mining expertise
- Supportive Govt mining license valid until 2036 (renewable)
- Access and compensation agreements with the 2 affected landowners
- Water 2.2 Mm³ /year sourced from aquifer via 90km pipeline
- 70/30 mix grid and solar produced onsite

Ongoing optimisation


- Initial design based on Phase 2 met test work (April 2023)
- Phase 3 test work (October 2023) indicates significant improvement
- Low-acid and high Cu irrigation
- Potential impact:
 - significantly reduced acid consumption, capex and opex
 - Improved recoveries, reduce leach times, smaller heaps
- Phase 4 test work bring to bankable standard (est. June 2024)
- BFS to be published Q3 2024



Ownership and Location




- Omitiomire deposit located northeast of Windhoek, accessible by ~140km of road, 100km to international airport
- Direct road links to Walvis Bay and Johannesburg (via Trans Kalahari Corridor)
- 5% held by a Namibian incorporated, independently managed community trust
- Greenstone is manager





- Flowsheet





Metallurgical Testwork



Phase 2 Test Work


- Completed April 2023
- 7x 4m and 1m sequential columns
- Results: implied 77% average Cu recovery, 44kg/tonne acid consumption and 300 day leach cycle time
- · Columns assayed at 1m intervals to establish leaching characteristics
- Majority of acid consumed in first meter lower 3 meters had no/little acid in irrigation solution despite continued good copper recoveries, by cupric to cuprous reaction

Phase 3 Test Work

- Completed October 2023
- May 2023 3x mini-columns using high Cu and low acid for irrigation: replicate cupric cuprous reaction
- Acid consumption reduced to 10kg/t
- Leach times reduced to 150 days (300 days)
- Recovery increased to 81%

Phase 4 Test Work

- Completion mid-2024
- 10x 4m columns
- 2 started Dec 2023, additional 8 columns in Feb 2024
- Expectation: Cu recoveries increase to 80+%, acid consumption reduced to 10-15kg/tonne, 200 day leach cycle time
- BFS published Q3 2024



Expected BFS Outputs




Technical

- Production: 25-30ktpa Cu cathode
- Life of Mine: 13-15 years
- Preproduction capital: \$360m
- Ave LOM sustaining capital: \$10m p.a.
- Ave LOM opex: \$4,650/tonne copper
- Plant Capacity: 6.7 Mtpa
- Metallurgical recoveries: 80%
- Acid consumption: 10-15 kg/tonne
- Acid plant capacity: 250 tpd
- Leach cycle time: 200 days
- Mining Strip ratio: 4.8:1
- Based on Owner Mining

Financial

- Post-Tax NPV8: \$175m (100%)
- Post-Tax IRR: 18%
- Capital Intensity 14,100/t Cu
- Key assumptions:
- Cu price \$4.5 /Ib LT
- FX: USD/ZAR 19:1

- Valuation upside not modelled:
- increased production/life of mine from reduced cut off grade
- No acid plant at all and buy acid domestically





Expected Capex/Opex Breakdown



Сарех				
Pre-Production Capex	USD (M)			
Plant Site, SXEW, Infrastructure	154.8			
Acid Plant	33.9			
Heap Leach Pad Construction	20.8			
Mining fleet, Workshops, WRD	59.2			
Road and River Diversions	9.8			
Pre-Strip and Capitalised Opex	17.4			
Water and power supply	32.1			
G&A, Land Acquisition and Access	17.9			
EPCM	12.3			
Total	358.1			

Opex			
Operating Costs	USD/t Cu		
Mining	2,441		
Processing	1,061		
Acid	275		
Power	636		
G&A, Camp, etc	235		
Total	4,648		

Sustaining Capex	USD (M)
Plant Site	5.8
Heap Leach Pad Construction	16.6
Mining Fleet	76.7
Closure Costs	24.0
Total	99.1

	USD/t Cu
C1 Costs	4,710
AISC	5,520

- Low Risk Infrastructure




Power

- Power requirement 25MW
- Proposal received from Nampower to connect to grid via approx. 70km line
- 30% of power to be provided by IPP solar supplier

Water

- Water to be supplied from Summerdown aquifer, approx. 90km to the east
- Extensive drilling and pump testing undertaken in 2023 to ensure water resource is sustainable







Craton Foundation Trust

- Owns 5% of Craton Mining and Exploration (Pty) Ltd
- Managed by independent trustees
- Founded 2010 to address social needs in area of influence of project
- Once mine in production steady stream of income will fund independent community initiatives (focus is on crime prevention and social health)

Community Engagement

- Omico holds regular community engagement with local stakeholders, including attending Farmers Association Meetings
- ESIA and ESMP being developed with local and regional stakeholders to IFC and World Bank Standards
- Application for environmental clearance to construct and mine to be submitted Q1 2024 – all specialist studies complete

Environmental

- Minimise water consumption in arid area closed system
- Evaporation management
- Heap leach uses 1/3 of water of conventional floatation
- Power supply 30% solar, 70% grid with supplementary power from acid plant heat
- Carbon emissions reduced through solar power when available
- Waste rock is essentially inert, no AMD or deleterious run-off



— Way Forward



	Q1 2024	Q2 2024	Q3 2024	Q4 2024	Q1 2025
Phase 4 Metallurgical Test Work					
Application for Environmental Clearance Certificate					
Final PDCs, Mass Balance and Flowsheets					
Negotiate Water Supply Access and Permits - Dept of Water Affairs					
Finalise Power Supply Negotiations - Nampower and IPP					
Update Mining Study, Optimisation, Reserves					
Update Engineering Study					
Update BFS, Capex and Opex					
Project Financing					
FID					





Thank You

For further information, please contact


Mark Sawyer – Greenstone msawyer@greenstoneresources.com

Mike Stuart – Omico m.stuart@omicomining.com





Appendix



Omitiomire Development and History



1970s: General Mining and Finance Corporation

· Soil geochem and shallow percussion and diamond drilling

1990s: Anglo American

• Geophysical surveys and further drilling, intersecting 106m @ 0.47% Cu

2008: IBML acquired Craton

- 85,000m new drilling
- Initial DMS and float metallurgical test work
- Mill-floatation PFS in 2010, small oxide DFS in 2013
- IBML development concept not compelling
- Tonnes and grade did not support capitally intensive mill-float development
- Project not advanced for 7 years
- Total spend of US\$18M

2019: Greenstone Investment

- Option over project acquired 2019, requirement to complete BFS with minimum spend of USD5m
- Total spend USD9m inc USD4m on engineering and USD1.3m on infill drilling
- · Identified chloride heap leaching as potential recovery method
- Focus on lower capital intensive heap leach with SX-EW to materially improve economics
- Comprehensive metallurgical test work programme (4 Phases)

Year	Drill Campaign	DD (m)	RC (m)	RAB (m)	PERC (m)	Total (m)
1976	Pre-IBML				889	889
1992	Pre-IBML	1,336			755	2,091
1993	Pre-IBML	224			986	1,210
1998	Pre-IBML		991			991
2007	IBML	737	9,485			10,222
2008	IBML	2,063	21,258			23,321
2009	IBML	1,484	6,868	832		9,184
2010	IBML: Oxide Infill		2,094			2,094
2010	IBML: Prospectus		4,294			4,294
2011	IBML: Resource Extension	5,753	6,114		1,676	13,543
2012	IBML: Resource Extension	4,478	4,729			9,207
2012	IBML: Metallurgical	1,117	1,058			2,175
2013	IBML: Oxide Infill		4,449			4,449
2014	IBML: Resource Extension		12,102			12,102
2022	Omico: Resource Infill		7,192			7,192
2022	Omico: Pit Geotechnical	1,415				1,415
		18,607	80,634	832	4,306	104,384




License Overview



License


- Mining License (ML197) granted March 2016 for 20 years (renewable for 15 year periods)
- Exploration license (EPL8550) granted Sept 2022 for 3
 years (renewable for up to 7 years in total with
 further renewals possible with ministerial discretion)
- Environmental Clearance Certificates granted to September 2025 (renewable) for exploration on both the ML and EPL
- Access agreement for Omitiomire farm signed until October 2024



Regional Geology




- Mineralisation in Ekuja Dome inlier, which covers an area of approximately 15km x 12km
- Dome is one of 3 dome-like gneisses penetrating through overlying high grade metasediments
- Rocks are mainly felsic gneiss and subordinate amphibolite and mafic schists (probably mafic volcanics)
- Dome system is similar to Sandfire's Mothero in Botswana and other regional deposits
- Deposit geology comprises two main rock packages:
 - Mafic rocks, hosting the Cu mineralisation, mainly of quartz, plagioclase, dark biotite and amphibole. Mineralised banding up to 100m thick
 - Surrounding leuco-gneisses usually unmineralized, quartz, plagioclase, variable amounts of biotite and trace amounts of garnet and sphene



- Omitiomire 2023 Copper Resource



- Updated resource based on Omico 2022 infill drilling
- Project has an CIM Definitions Standard compliant resource estimate containing 490kt copper
- Strike length of 3.5km, open at depth



Unsliced cross section to the NE - upwards convex lens shape of mineralisation

OS1 and OS2 - high grade shoots

BT - disconnected hangingwall mineralised zone

Red: >0.5% Cu

Yellow: 0.1% - 0.5% Cu

Blue: < 0.15Cu

All tabulated data have been rounded and as a result minor computational errors may occur

Notes 1. Mineral Resources, which are not mineral reserves, have no demonstrated economic viability

2. The Mineral Resource is reported for mineralisation contained within a Whittle optimised pit shell above a cut-off grade of 0.29% Cu, which is based on a copper price of USD 4.4/lb, mining costs of USD 1.91/t at pit rim (escalated with depth), treatment costs to cathode of USD 17.0/t ROM ore (including G&A), 3% royalty, 0.04 USD/lb cathode sales cost, 100 USD/t cathode transport cost, pit slope 52° to 60°, mining dilution 3%, mining recovery 95%, copper recovery 76.9%.

— Mining




- Conventional drill and blast, truck and shovel open pit operation with staged pit designs
- 1,400m of diamond drilling used for pit slope analysis
 - Excellent rock conditions and low pore water pressures
 - steep walls
- 15m benches mined in 5m flitches for ore
- Ground water hydrogeology indicates no significant inflows into the open pit
- Waste rock is essentially inert
 - Little capacity to generate any acid, or other deleterious elements
 - Limited migration of any solute from the waste facilities
- Final pit design based on footwall ramps
 - Minimises waste mining
 - Interim pushbacks with temporary hangingwall ramps




Phase 2 Metallurgical Results



- 1x oxide 4m column, 7x sulphide 4m columns
- Range of Cu head grades (0.3%Cu, 0.6%Cu and 0.9%Cu)
- Parallel Im sequential columns replicating the conditions in the 4m columns
- 30-day curing period with NaCl and dilute sulphuric acid (3 days for oxide with acid only)
- Sulphide METSIM simulation PDC
- **76.9% Cu** recovery
- 307 day leach cycle
- 43.9kg/t acid consumption
- Oxide METSIM simulation PDC
 - 86% Cu recovery
 - 167 day leach cycle
 - 48.7 kg/t acid consumption






Upside Phase 2 Results



- Phase 2 sequential column results:
- Nearly all acid was consumed in the first 1m of the column
- But in lower ¾ of column dissolution of copper continued
- Dissolution of Cu under low acid conditions driven by cupric to cuprous reaction
- Potential identified to leach using low-acid, high Cu irrigation solution on the heaps


	Cu Recovery	Acid Consumption	Average Irrigation Acid Concentration
Average 1st Metre	84%	90 kg/t	7.9g/I
Average 2 nd Metre	70%	19 kg/t	0.9g/I
Average 3 rd Metre	70%	17 kg/t	0.3g/I
Average 4 th Metre	70%	16kg/t	0.2g/I
Average 2 nd -4 th Metre	70%	17kg/t	0.4g/l




- 2023 Phase 3 Testwork-Low Acid Proof of Concept



- Commenced May 2023
- 3 mini-columns (30cm high) with average grade (0.6% Cu)
- 30 days curing with the NaCl solution and high grade Cu
 (20g/I), low grade acid solution (1g/I)
- Irrigation with Test work 10g/I Cu and 0.5g/I acid content solution.
- All columns recovered over 80% of the total copper at an average acid consumption of 11kg/t
- METSIM simulation acid consumption may reduce to 10 to 15kg/t from the current 44 kg/t, with reduction in leach time to less than 250 days.






Current Processing Route




- Conventional agglomeration with a salt brine and dilute acid
- Stacking via grasshoppers on heap leach pad (HLP) - with an impermeable clay base and 2x HDPE plastic liners and a leak detection system, with a height of 6m per lift
- 30 days curing (7 days for oxide) heap irrigated with initially Intermediate Leach Solution (ILS), followed by raffinate, for up to 300 days
- Resultant Pregnant Leach Solution (PLS) is processed through a conventional Solvent Extraction and Electrowinning (SXEW) plant to produce copper cathode

- Open pit to the right with waste rock dump,
 pit exit leading to the ROM pad
- Foreground is the mining cluster, including workshops, equipment parking, etc.
- Background shows the HLP with the ponds,
 SXEW, sulphur storage and acid plants



Current Processing Route





ROM Pad (RHS) Ponds, SX and EW




Acid & sulphur storage, acid plants (LHS)
Crushing circuit and crushed ore stockpile (RHS)

- Omitiomire 2023 Copper Resource



- Diversion of Black Nossob ephemeral river which currently flows through the open pit area
- Channel designed to for 1:200-year flood from the 3 catchments in the area of the pit
- The channel is up to 40m in total width, with a berm where needed

Typical River Diversion Channel and Berm WHES SPLECTED WATERAL ONLY HOUSE 10 550 MOD AGRID TYPICAL CHANNEL (A) AND BERM (SOUTH) SECTION SPALE 1200



- Key Technical and Environmental Consultants



Internationally recognised experts with a strong track record in copper hydrometallurgy

METC Antalogue Engrang Rivering & Calmerine	BFS Study Manager	Heap leach, process plant and infrastructure design Capex and Opex costs
BARA	Mining	Pit optimisation, design & scheduling, infrastructure Reserve estimation, Capex and Opex costs
THE MSA GROUP	Geology and Mineral Resources	Drill planning and Supervision Resource Estimation
MJO SE INGENIERIA Y CONSULTORES EN METALLIROIA	Metallurgical Consultants	Metallurgical programme design and implementation Process development, PDC, mass balance
ECC ENVIRONMENTAL COMPLIANCE COMPULTANCY	Environmental & Social	Monthly monitoring, ESIA and ESMP Baseline, specialist & closure studies
Knight Piésold	Geotechnical	River and road diversion design Leach pad and process plant geotechnical studies
CREO ENGINEERING SOLUTIONS	Engineering	Water supply Power supply and solar



– Location



- Stable mining jurisdiction, democratic government, independent, strong legal system
- Government supportive of mining sector, 12% of GDP (2022)
- Well trained workforce, experience of heap leach and SXEW
- Ranked 3rd in Africa in the Fraser Institute's 2022 Policy Perception Index
- Low population density: Population of 2.5m across 825,000km2
- Well-connected and functional infrastructure with key road and shipping access
- Newly upgraded deep water port at Walvis Bay





















